

Index

- activation energy 11, 319
- active electronic device function 273
- all-epitaxial dopant-based quantum dots 70–71
- Anderson–Mott transition 6–7
- antimony 262, 266, 268
- APT *see* atom probe tomography
- artificial atoms 25, 71, 241–42
- atom map 162, 164, 175–77
- atom probe, local electrode 157
- atom probe tomography (APT) 3, 151–60, 165, 177, 179–80
- atomic-scale silicon devices 2, 61–62, 64, 66, 68, 70, 72, 74, 76, 78, 80, 82
- atoms, single-dopant 212, 341
- atomscope 180

- back-gate voltage 314, 320
- background dopants 31–32
- band minima basis (BMB) 53
- beam-line (BL) 175, 178–79
- bias voltage 72, 219, 334, 336–37
- BL *see* beam-line
- Bloch states 221
- BMB *see* band minima basis
- Bohr radius 46, 53, 80, 123–24, 223, 236, 242–43, 318, 320
- boron, lateral dopant profile of 175–76
- bulk donors 43, 46, 50, 52, 54, 221–22

- bulk silicon 6, 8, 11, 13, 43, 63, 77, 244–46
- bursts, secondary electron 126

- cantilever 269–71
- carry-in digit 337, 340
- CB *see* Coulomb blockade
- channel
 - edge 216
 - effective 217
 - physical 217
 - transistor 261–62
 - undoped 232, 236–37
- channel dopant distribution 160, 166
- channel doping, intentional 234, 237
- channel region 91, 98, 100–3, 105–6, 108, 152, 160, 162, 164, 166, 171–73
 - active 90, 109–10
- charge carriers 131, 139, 216–17
- charge qubits 21
- charge sensors 23–24, 265
- charge states 20, 80, 134, 212, 243, 317
- charge transitions 76–77, 82
- chemical vapor deposition (CVD) 282
- CMOS processes for single-atom transistors 233, 235, 237
- CMOS technology 91, 190, 197, 201, 203–4, 248

- coherence of donor spins 260–61, 263–64
- coherence times 259, 261, 269, 288, 290, 294
- coherent control 121, 281–82, 295
- coherent oscillations 33
- coherent passage of information 25, 27, 29
- coherent tunneling by adiabatic passage (CTAP) 26, 140–41
- conductance 14–16, 25, 72, 82, 241, 335
- conduction band 11, 111, 213, 236, 245–47
- conduction electrons, wavefunction of 11, 15, 261–62
- confinement 11, 13, 48–49, 70, 73, 216, 268, 330
 - interfacial 49–50
- control, single-dopant 89, 91
- conversion, spin-to-charge 22, 24, 80, 224
- Coulomb blockade (CB) 15–16, 43, 45, 47, 71, 110–11, 219, 241, 335
- Coulomb blockade oscillations 17, 72
- Coulomb potentials 104–5, 110
- coupled donor–quantum dot spin qubits 257, 259
- coupled donors 3, 257
- critical constraint 125, 127–28
- cryogenic CMOS amplifiers 200–1, 203, 205
- cryogenic temperatures 3, 71, 112, 187–88, 191, 200–2
- cryostat 188, 200–2, 205–7, 340
- CTAP *see* coherent tunneling by adiabatic passage
- CVD *see* chemical vapor deposition
- dangling bond (DB) 64, 69, 284
- DB *see* dangling bond
- decoherence 30–32, 63, 127, 188, 259, 288, 290
- density functional theory (DFT) 67
- detection efficiency 93–94, 102, 139, 179
- deterministic doping 89–91, 114, 134, 242
- deterministic single-atom devices 78–79
- deterministically implanted single donors 110–11
- device currents 271
- device downscaling 80, 330
- device fabrication 69, 91, 136, 214, 264–65
 - atomic-scale silicon 65
 - donor–dot 264
- device functionality 330–31
- device geometry 74, 78, 136–37, 203, 212, 273
- device integration of donors 260
- device layer, thin natural silicon 264
- device source/drain potentials 213
- devices
 - atomic-scale 70
 - decananometric-channel 14
 - diamond-based 295
 - donor–quantum dot qubit 259
 - double-quantum dot 265
 - extending doped-channel 109
 - few-atom 329–30
 - few-donor quantum dot 226
 - nano-electronic 82
 - nanoscale 102, 263, 315
 - optical 120, 140
 - silicon quantum information 3
 - single-donor 70, 78–80, 222
 - single-dopant 114
 - single-dopant controlled 114

- two-donor 110–11, 129
- undoped-channel 217
- DFT *see* density functional theory
- diamond 3, 20, 256, 281–86, 288, 290, 292–296
 - synthetic 282
 - ultrapure 285, 291, 293
- diamond defects 292–93
- diamond quantum devices 296
- diamond quantum registers 289, 294
- diamond spins 289, 295–96
- distance
 - donor–interface 309
 - interdonor 10, 21, 309
- donor arrays 21, 62–63, 311
- donor atom 14, 33, 121, 125, 154, 231, 244, 266, 269, 308, 323
- donor-based memory devices 309
- donor-based quantum
 - computation architectures 78, 83
- donor-based quantum computer
 - architectures 63, 221
- donor-based qubits 80, 226
 - functional 64
- donor-based qubits in silicon 20
- donor charge states 314
- donor core 50, 80
- donor–dot devices 269
- donor electron spin coherence
 - times 262
- donor electron spin relaxation
 - 260, 263
- donor electron spin relaxation
 - times 260
- donor electrons, bound 121
- donor ground state 11
- donor quantum dots (DQDs) 13, 29
- donor qubits 46
- donor qubits in silicon 45
- donor spin qubit applications 266
- donor spin qubits 52, 256
- donor spins 23, 256, 260–61, 263
- donor states 44, 48–49, 55, 220
 - charged 217, 224
- donor wavefunctions 44, 46, 52–54, 221
- donors
 - electron-bound 35
 - implanted 110, 121, 128–29, 131, 141
 - ionized 28, 307, 314, 317
 - isolated 111, 247
 - shallow 7, 243–44
 - single-gated 226
- dopant atoms, uncontrolled 127
- dopant-based devices 73, 75, 77
- dopant-based electronics 306, 312
 - integration of 306
- dopant-based optoelectronics 307, 321, 323
- dopant diffusion 68, 113, 215
- dopant distribution 91, 104–5, 160–61, 163, 165–67, 169, 171, 173, 175, 178, 313
 - discrete random 107, 109
 - ordered 104, 106, 109
 - random 91, 104, 107, 109
- dopant distribution in FinFETs 174–75, 177
- dopant fluctuation 160, 171, 174
- dopant ions 105, 109
- dopant nanowires 65, 70
- dopant-rich environments 306–7, 309, 311, 313
- dopant structure, buried
 - STM-patterned 66, 68
- dot, few-donor 74, 80–81
- double-donor system 319, 321
- downscaling of dopant-based
 - devices 73, 75, 77
- DQDs *see* donor quantum dots
- dynamic shadow mask 268–69, 271

- EBL *see* electron-beam lithography
- EDMR *see* electrical detection of magnetic resonance
- effects, single-donor 238, 243
- electrical detection of magnetic resonance (EDMR) 261–63
- electron-beam lithography (EBL) 65, 127–28, 234, 270
- electron-hole pairs 102, 124, 305, 315, 318
- electron reservoir 23
- electron shuttling 256, 259
- electron spin coherence 260, 263
- electron spin qubits 22–23, 25, 31
- electron spin resonance (ESR) 34, 42, 141, 260, 292
- electron spins
 - donor-bound 34
 - individual 35
 - single-donor 119
- electron tunneling 81–82
- electron wavefunction 15, 220
- electronic devices
 - conventional 312
 - modern silicon-based 61
- electronic spins 42, 45, 284
- electrons
 - donor-bound 34, 49, 261
 - photoexcited 318
 - photon-excited 317, 321
 - single-donor 256
- electrostatic discharge 102, 137
- energy
 - excited-state 219
 - ground-state 26, 45, 241, 245
 - implant 125, 266
 - photon 315–16
- epitaxial silicon environment 64, 83
- ESR *see* electron spin resonance
- exchange coupling 63, 256, 259, 268–69
 - donor-dot 258, 264, 268
- feedback loop 196, 198–99
- feedback resistor 204–6
- Fermi energy 18, 26, 245
- FETs
 - carry-in 337
 - donor-rich-channel 309
- FETs *see* field-effect transistors
- FIB *see* focused ion beam
- field-effect transistors (FETs) 42, 61, 103–4, 107–8, 151, 191, 195, 212, 231, 261–62, 268, 308, 336–38, 340
- field evaporation 156–57
- field regimes 47–48
- FinFETs 1–2, 174–75, 177, 211–14, 222–24, 226, 273, 340–41
 - state-of-the-art silicon 335
- focused ion beam (FIB) 92–93, 98, 126, 155, 158, 270
- functionalities, dopant-based 306–7
- gate oxide film 162, 168
- HDD *see* highly doped drain
- highly doped drain (HDD) 233, 236, 238
- HRF *see* hyperfine resonance frequency
- Hubbard bands 7, 10–11
 - upper 11, 29
- hyperfine coupling 52–53, 284
- hyperfine resonance frequency (HRF) 53–54
- hyperfine Stark effect 42, 46, 51, 53
- IBIC *see* ion beam-induced charge
- implant dopant ions 90–91

- implanted ions 92–95, 103, 107, 110, 123–24, 127–28, 131, 133–34
- individual dopant atoms 305–7, 321
- individual dopant potentials 313
- individual dopants 2–3, 5–6, 8, 10, 12, 14, 16, 18, 20–22, 24, 26, 28, 91, 152–53, 312
- interaction Hamiltonian 33–34
- interface, gate–channel 220
- ion beam–induced charge (IBIC) 128, 135
- ion implantation 102, 121, 123, 128, 131, 133–34, 140, 160, 172, 175, 266, 269–71
 - conventional 95
- ionization energy 29, 111, 114, 213, 243–47, 285
- isolated donor regime 7

- JFETs *see* junction field-effect transistors
- junction field-effect transistors (JFETs) 189

- LDD *see* lightly doped drain
- LEAP *see* local electrode atom probe
- lightly doped drain (LDD) 233, 236
- local electrode atom probe (LEAP) 157–58, 165, 180
- loop gain 194–95, 197
- low-noise transimpedance amplifiers, design rules for 193, 195

- magnetic resonance imaging (MRI) 292, 295

- memory devices
 - dopant-based 309
 - single-electron 308
- metal-oxide-semiconductor field-effect transistors (MOSFETs) 1, 41, 90, 122, 124, 134, 153, 160–61, 163, 165, 167, 212–13, 233
- metastable singlet states 284, 287–88
- MOSFETs *see* metal-oxide-semiconductor field-effect transistors
- MRI *see* magnetic resonance imaging

- n-MOSFETs 160–62, 166, 168–72, 174, 204
- nanodevices 187, 200–1, 206, 312
- nanoelectronic devices 3
 - conventional integrated 61
 - single-dopant 2
- neutral donor state 226
- nitrogen atoms 282, 284
- noise 26, 188, 191–92, 195–96, 199–200, 204–6, 261, 322
 - flicker 204–5
 - high-frequency 200, 206
- nuclear spin memory 257–58
- nuclear spins 5, 20, 22, 31, 34, 45, 51, 62–63, 120–22, 126, 256–57, 259–61, 288–89

- operational amplifier 192–95, 200, 204–5
- optical transitions 284–87, 296
- optoelectronic devices 321
 - dopant-based 321
- ordered arrays 103, 212
- ordered dopant arrays 65, 70, 102–3, 105

- p-MOSFETs 160–62, 166, 168–71, 173–74, 204
- phosphorus donors 62, 75, 131, 214, 259
- phosphorus ions 106
- photon absorption 315–16
- photon detection 305, 307, 314
- photon-excited electron capture in individual donors 317
- photon illumination 314–15, 317, 319, 321
- polysilicon gates 234, 236, 246
- position-sensitive detector (PSD) 157, 179
- PSD *see* position-sensitive detector

- QDs *see* quantum dots
 - donor-induced 309, 318
- QND *see* quantum nondemolition
- QPCs *see* quantum point contacts
- quantum computation 62, 83, 119–21
- quantum computer devices 126, 128
- quantum computing 2–3, 119–20, 122, 124, 126, 128, 130, 132, 134, 136
 - cluster-state 257, 259
- quantum computing applications 42, 331
- quantum devices 3, 140, 188–89, 200–1, 207
 - donor-based 42
 - ultrasmall silicon 77
- quantum dot-like states 222
- quantum dots (QDs) 25–26, 70–71, 74–77, 187–88, 207–8, 255–60, 262–64, 268–70, 272–74, 315–16
 - few-donor 77–78, 80
- quantum gates 290
 - universal 19
- quantum logic gates 5, 19, 21
- quantum nanodevices 187–88
- quantum nondemolition (QND) 33–35
- quantum point contacts (QPCs) 121, 188–89
- quantum states 6, 20–21, 25, 46, 121, 134, 140, 187–89, 238, 282
- quantum technologies 20, 295
- quantum transport 15, 110–12, 140
- qubits 5, 19, 21–22, 25, 30–31, 33–34, 42, 49–50, 62–63, 119–22, 127, 255–56, 288–89, 291, 295

- random channel dopings 103, 105
- random dopant fluctuation (RDF) 1, 90, 114, 160, 166, 171
- random telegraph signal (RTS) 315–20, 322
- rapid thermal anneal (RTA) 132–33, 266
- RDF *see* random dopant fluctuation
- resistors, poly-silicon 203–4
- room-temperature instrumentation 188–89, 200, 207
- RTA *see* rapid thermal anneal
- RTS *see* random telegraph signal
- RTS jumps 315–16, 319

- SATs *see* single-atom transistors
- scanning electron microscopy (SEM) 130, 155, 213, 234, 308
- scanning probe microscopy (SPM) 152
- scanning spreading resistance microscopy (SSRM) 152–53
- scanning transmission electron microscopy (STEM) 152, 180

- scanning tunneling microscopy (STM) 2, 14, 64, 82, 152–53, 242, 312
- secondary electron detection 96, 100, 273
- secondary electron detection efficiency 95–96, 98, 100
- secondary electron emissions 96–97
- secondary electrons 92–94, 96–99, 124, 126, 273
- secondary ion mass spectrometry (SIMS) 163, 165, 177, 266
- SEM *see* scanning electron microscopy
- semiconductor devices, on-state 99
- semiconductors 5–6, 89–90, 180, 202, 305–6
- SII *see* single-ion implantation
- silicon 5–9, 18–21, 41–46, 62–64, 121–22, 226–29, 255–60, 266–68
- silicon bandgap 10, 98, 101
- silicon-based electronic devices 151
- silicon-based semiconductor devices 151
- silicon-based single-dopant devices 3
- silicon-based single-dopant devices and integration 305–6, 308, 310, 312, 314, 316, 318, 320, 322
- silicon CMOS devices, advanced 233
- silicon crystal 6–7
- silicon devices 3, 13, 15, 17, 26, 78, 82
 - conventional 61
 - nanometric 6
 - natural 141
- silicon nanostructures 188, 243, 305, 309
- silicon nanowire devices 270
 - etched 271
- silicon nanowires 270
- silicon quantum dots 13, 221
- silicon quantum wells 263–64
- silicon technology 1, 20
- silicon transistors 11, 110–11
- SIMS *see* secondary ion mass spectrometry
- single-atom devices 3, 141, 329–32, 334–36, 338, 340–42
- single-atom devices for circuits 331, 333
- single atom imaging 151–54, 156, 158, 160, 162, 164, 166, 168, 170, 172, 174, 176, 178, 180
- single-atom transistors (SATs) 64, 233, 235, 237, 241, 330–31, 334, 341–42
- single diamond spins 293
- single-donor electron-tunneling 138
- single-donor transistors 308, 314
- single donors 3, 24, 46, 79, 211–12, 214, 216–26, 242, 257, 266–69
- single-dopant-based electronic applications 90
- single-dopant transport 214–15, 241
- single dopants 3, 42, 78–79, 212, 214–15, 226, 239, 307, 312
- single-electron spins 256, 287–89
- single-electron transistors 35, 72, 121, 188, 212, 330
- single-electron tunneling 110, 307, 309, 317–18
- single-electron tunneling conduction 321–22
- single-electron tunneling transport 306, 309
- single-electron turnstile, donor-based 310

- single-ion impacts 131, 133, 137, 139, 265, 271
- single-ion implantation (SII) 2, 21, 28, 92–96, 101–4, 112–13, 119–20, 123, 125, 127–31, 133–35, 140–41, 242, 271, 282
- single-photon detection 306, 315, 317, 321, 323
- single spins 22, 281, 294
- single spins in diamond 281–82, 286, 288, 290, 292, 294, 296
- solid-state devices 120
- spacers 216, 234, 236–37
- spin quantum bit architecture 255–56, 258, 260, 262, 264, 266, 268, 270, 272
- spin readout device 24
- spin states
 - excited 22–23
 - nuclear 20, 34, 256, 289
- SPM *see* scanning probe microscopy
- SSRM *see* scanning spreading resistance microscopy
- Stark-shifted spectrum 48, 50
- states
 - donor-bound 51
 - donor-confined 221
 - donor-interface 225
- STEM *see* scanning transmission electron microscopy
- STM *see* scanning tunneling microscopy
- STM lithography 65–67, 71–72, 78–80, 83
- STM-patterned devices 70, 78
- stochasticity 241–43
- TEM *see* transmission electron microscopy
- thermal noise 189, 191, 196, 199–200, 204–6
- three-donor array 26, 29
- three-donor devices 28, 141
- transconductance 107, 109
- transimpedance amplifier 192–96, 199–200, 204–6
- transistors
 - single-atom 78, 231, 335, 337, 339
 - single-dopant 2–3, 306–7, 314
- transmission electron microscopy (TEM) 137, 152, 234
- transport, electronic 78
- transport donor 307–9, 317, 320–21
- transport dopant 307
- transport electrodes 64, 78
- transport spectroscopy 217, 224, 231, 245–47
 - low-temperature 238, 243–44
- tunnel barriers, source-side 322
- tunnel gaps 71, 74–76
- two-electron donor spectrum 217
- two-electron donor state 224
- two-electron states 9, 23, 224–25
- valley splitting 13, 222, 226, 243
- wavefunction
 - dot electron 268–69
 - electronic 221, 244
 - single-donor ground-state 9
- wide-band transimpedance amplifiers 196–97, 199